



More compact & Much lighter

- 💡 Dimensions: 344*274.5*123 mm
- 💡 Weight: 8kg

Wider working voltage range & Quicker start to work

- 💡 MPPT voltage range: 80-400V
- 💡 Starting voltage: 80V

Better Monitoring System with easier to operate

- 💡 Innovatory WiFi solution
- 💡 User-friendly interface

NS Series

Single-MPPT, Single-Phase
1.0kW/1.5kW/2.0kW/2.5kW/3.0kW

- Maximum Efficiency up to 97.5%
- European Efficiency up to 97.0%
- MPPT Efficiency up to 99.9%
- Fanless Design
- Lower noise emission
- IP65 protection standard
- Integrated WiFi monitoring solution
- Integrated DC switch

Standard 10-year Warranty

Integrated WiFi Solution

Online monitoring system and mobile Apps



WHERE THE SUN SHINES, THERE IS GOODWE!

Technical Data

GW1000-NS

GW1500-NS

GW2000-NS

GW2500-NS

GW3000-NS

DC Input Data

Max. DC power(W)	1200	1800	2300	2700	3200
Max. DC voltage (V)	450	450	450	500	500
MPPT voltage range (V)	80~400	80~400	80~400	80~450	80~450
Starting voltage (V)	80	80	80	80	80
Max. DC current (A)	10	10	10	18	18
No. of DC connectors	1	1	1	2	2
No. of MPPTs	1	1	1	1 or 2	1 or 2
DC connector	MC/AMPHENOL				

AC Output Data

Norminal AC power(W)	1000	1500	2000	2500	3000
Max. AC power(W)	1000	1500	2000	2500	3000
Max. AC current(A)	5	7.5	10	12.5	13.5
Norminal AC output	50/60Hz; 230Vac				
AC output range	45~55Hz/55~65Hz; 180~270Vac				
THDi	<3%				
Power factor	0.9 leading~0.9 lagging				
Grid connection	Single phase				

Efficiency

Max. efficiency	96.5%	97.0%	97.0%	97.5%	97.5%
Euro efficiency	96.0%	96.0%	96.0%	97.0%	97.0%
MPPT adaptation efficiency	99.9%				

Protection

Residual current monitoring unit	Integrated
Anti-islanding protection	Integrated
DC switch	Integrated (optional)
AC over current protection	Integrated
Insulation monitoring	Integrated

Certifications&Standards

Grid regulation	G83/2, VDE0126-1-1, AS4777.2&.3, EN50438, ERDF-NOI-RES_13E;	G83/2, VDE0126-1-1, AS4777.2&.3, EN50438, ERDF-NOI-RES_13E;
Safety	According to IEC62109-1&-2, AS3100	
EMC	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3	

General Data

Dimensions (WxHxD)	344*274.5*123 mm	
Weight (kg)	8	9
Mounting	Wall bracket	
Ambient temperature range	-25~60°C(>45°C derating)	
Relative humidity	0~95%	
Max. operating altitude	2000m	
Protection degree	IP65	
Topology	Transformerless	
Night power consumption(W)	<1	
Cooling	Nature convection	
Noise emission(dB)	<25	
Display	LCD	
Communication	USB2.0; WiFi/RS485 (optional)	
Standard warranty(years)	10/15/20/25(optional)	