

Tigo Energy[®] Module Maximizer[™]-ES (MM-ES)

Data Sheet



The Tigo Energy output optimization starts with dynamic module balancing – a Module Maximizer (patented) attached to each module manages the energy harvest and sends information to the Maximizer Management Unit for reporting and control. The Tigo Energy Serial Module Maximizer (MM-ES) connects in a series topology. MM-ES maintains best-in-class system conversion efficiencies.

The Tigo Energy Module Maximizer includes a unique technology (patented) which greatly enhances the safety of a PV solar installation. As part of the Tigo Energy Maximizer system, this function can be activated with a safety button or via a remote management console. The system can be installed, maintained or approached by fire personnel without the exposure to voltage levels typically in excess of 400 volts.

The Tigo Energy Module Maximizer is packaged in a NEMA3R enclosure (water and weather resistant), conforms to UL and IEEE safety standards. There are Module Maximizer options to fit any PV module, crystalline silicon or thin-film, regardless of output voltage or nominal power rating.



Ask your PV Solar distribution partner for the Tigo Energy Module Maximizer preinstalled on many of their most popular framed solar panels for simple on-site system installation for your new or existing PV system. Also watch for modules that include the Tigo Energy technology fully integrated into the junction-box – available soon from leading PV module manufacturers.

Module Maximizer-ES Technical Specifications

Input data	MM-ES50	MM-ES75	MM-ES110	MM-ES170
Maximum power	350W	350W	350W	350W
Maximum input DC voltage (Voc)	52V	75V	110V	170V
Vmp range *	16-48V	30-65V	30-89V	30-140V
Maximum continuous current (Imp)	9.5A	6.5A	4.7A	2.6A
Maximum input current (Isc)	10A	7.5A	5A	ЗA

* Vmp = Voltage at maximum power = Maximum power voltage

Output Data (DC)				
Maximum output power	350W	350W	350W	350W
Maximum continuous current	9.5A	6.5A	4.7 A	2.6A
Nominal Voltage/range	0 - Voc	0 - Voc	0 - Voc	0 - Voc

-30°C +70°C Natural Convection

IP-65, NEMA3R

Mechanical Data Operating temperature range Cooling Enclosure environmental rating

Features

Compliance


Panel connector Bus connector er UL1741

FCC part 15, class B
EN 61000
NEC 2008 compliant MC4 compatible
(for retrofit) MC3 connectors
NEC 2008 compliant 40AMP

Specifications subject to change. Always check the table on the Tigo Energy Module Maximizer label for specifications as supported by that particular unit.

Optimize the energy harvest of your PV system using the Tigo Energy Maximizer to:

- accelerate system payback
- maximize the power output of individual modules
- reconsider previously rejected projects because of unfavorable shade or orientation
- maintain best-in-class conversion efficiency
- manage the system with module-level data to minimize operational costs and keep the system at peak performance throughout its lifetime
- introduce an unprecedented level of safety for new and existing PV solar installations (patented)
- simplify the balance-of-system design, especially for high Voc or thin-film modules





Tigo Energy, Inc. P +1.408.402.0802 | F +1.408.358.6279 420 Blossom Hill Road, Los Gatos, CA 95032 U.S.A. www.tigoenergy.com contact@tigoenergy.com

Printed on recycled paper

MMES-03.07.12-V14

Copyright © 2012 Tigo Energy, Inc. All rights reserved.